



Dart Aerospace Ltd.
1270 Aberdeen St
Hawkesbury, ON
K6A 1K7
Canada

Tel (613) 632-5200
Fax 613 632-5246



D407-667-205TRN
Job Sheet 193312



Part No: D407-667-205TRN

Job Qty: 1 pcs

Part Name: Crosstube Turning Detail



Part Weight: 0 lbs

Status: New

Priority: Medium

Job Created: 4/10/19

Job Tracking No:

Due Date: 4/18/19

Created By: Jason Leroux

Type: Stock

Description:

Note: DWG REV G IPP Rev:A 08-03-06 new issue DD verified by:ec IPP Rev B 08.04.02 Removed polish EC verified by: DD IPP Rev:C 08-08-19 revE as per dwg DD verified by:EC

Ship Via:

Bill of Materials

Job Routing

Op No	Operation	Qty	Start Date	Due Date	Standard		Workcenter/Supplier		Lead Time	DAS Sign-off
					Setup Hrs	Run Hrs	Workcenter / Supplier			
100	Mori Seiki TL-40 - 1	1 pcs	4/18/19	4/18/19	2.49	3.13	Mori Seiki TL-40 - 1			662019-04-23
110	QC 2	1 pcs	4/18/19	4/18/19	0.00	0.00	QC 2 - 1			9-89
							QC 2 - 12			
							QC 2 - 14			
							QC 2 - 17			
							QC 2 - 19			
							QC 2 - 2			
							QC 2 - 20			
							QC 2 - 22			
							QC 2 - 23			
							QC 2 - 25			
							QC 2 - 32			
							QC 2 - 33			
							QC 2 - 35			
							QC 2 - 39			
							QC 2 - 4			
							QC 2 - 40			
							QC 2 - 44			
							QC 2 - 45			
							QC 2 - 48			
							QC 2 - 49			
							QC 2 - 50			
							QC 2 - 51			
							QC 2 - 52			
							QC 2 - 57			
							QC 2 - 62			
							QC 2 - 63			
							QC 2 - 8			DAS
							QC 2 - 66			662019-04-23
							QC 2 - 64			9-89

Plex 4/10/19 12:39 PM dart.leroux.jason

				QC 2 - 65		
				QC 2 - 5		
				QC 2 - 71	DAS	
120	Mori Seiki TL-40 - 1 - B4B	1 pcs	4/18/19	0.00 3.13	Mori Seiki TL-40 - 1 - B4B	66 2019-04-24
130	QC 2	1 pcs	4/18/19	0.00 0.00	QC 2 - 1	9-89
				QC 2 - 12		
				QC 2 - 14		
				QC 2 - 17		
				QC 2 - 19		
				QC 2 - 2		
				QC 2 - 20		
				QC 2 - 22		
				QC 2 - 23		
				QC 2 - 25		
				QC 2 - 32		
				QC 2 - 33		
				QC 2 - 35		
				QC 2 - 39		
				QC 2 - 4		
				QC 2 - 40		
				QC 2 - 44		
				QC 2 - 45		
				QC 2 - 48		
				QC 2 - 49		
				QC 2 - 50		
				QC 2 - 51		
				QC 2 - 52		
				QC 2 - 57		
				QC 2 - 62		
				QC 2 - 63		
				QC 2 - 8	DAS	
				QC 2 - 66	66 2019-04-24	
				QC 2 - 64	9-89	
				QC 2 - 65		
				QC 2 - 5		
				QC 2 - 71		
140	QC 8	1 pcs	4/18/19	0.00 0.00	QC 8 - 12	
				QC 8 - 14		
				QC 8 - 17		
				QC 8 - 20		
				QC 8 - 25		
				QC 8 - 3		
				QC 8 - 32		
				QC 8 - 33		
				QC 8 - 35		
				QC 8 - 39		
				QC 8 - 4		
				QC 8 - 44		
				QC 8 - 45		
				QC 8 - 49		
				QC 8 - 58		
				QC 8 - 8		
				QC 8 - 9		
				QC 8 - 68	DAS	
				QC 8 - 67	67 19-04-25	
				QC 8 - 1 (A)	9-89	
				QC 8 - 47		
				QC 8 - 40		
				QC 8 - 52		
					</	

				QC 8 - 23	
145	Crosstubes - 2 - B4B	1 pcs	4/18/19	0.00 0.65	Crosstubes - 1 - B4B
					Crosstubes - 2 - B4B
					Crosstubes - 3 - B4B
					Crosstubes - 4 - B4B
150	Crosstubes - 3 - B4B	1 pcs	4/18/19	0.00 0.25	Crosstubes - 1 - B4B
					Crosstubes - 2 - B4B
					Crosstubes - 3 - B4B
					Crosstubes - 4 - B4B
160	QC 7	1 pcs	4/18/19	0.00 0.00	QC 7 - 10
					QC 7 - 13
					QC 7 - 14
					QC 7 - 15
					QC 7 - 17
					QC 7 - 18
					QC 7 - 19
					QC 7 - 2
					QC 7 - 28
					QC 7 - 3
					QC 7 - 30
					QC 7 - 34
					QC 7 - 36
					QC 7 - 37
					QC 7 - 41
					QC 7 - 47
					QC 7 - 48
					QC 7 - 51
					QC 7 - 58
					QC 7 - 59
					QC 7 - 60
					QC 7 - 9
					QC 7 - 68
					QC 7 - 50
					QC 7 - 67
					QC 7 - 40
170	Packaging 3-1 - Stock - B4B	1 pcs	4/18/19	0.00 0.00	Packaging 3 - 1 - B4B
					Packaging 3 - 2 - B4B
					Packaging 3 - 3 - B4B
					Packaging 3 - 4 - B4B
					Packaging 3 - 5 - B4B
					Packaging 3 - 6 - B4B
					Packaging 3 - 7 - B4B
					Packaging 3 - 8 - B4B
					Packaging 3 - 9 - B4B
					Packaging 3 - 10 - B4B
					Packaging 3 - 11 - B4B
					Packaging 3 - 12 - B4B
					Packaging 3 - 13 - B4B
					Packaging 3 - 14 - B4B
					Packaging 3 - 15 - B4B
					Packaging 3 - 16 - B4B
					Packaging 3 - 17 - B4B
					Packaging 3 - 18 - B4B
					Packaging 3 - 19 - B4B
					Packaging 3 - 20 - B4B
					Packaging 3 - 21 - B4B
					Packaging 3 - 22 - B4B
					Packaging 3 - 23 - B4B
					Packaging 3 - 24 - B4B

				Packaging 3 - 25 - B4B	
				Packaging 3 - 26 - B4B	
				Packaging 3 - 27 - B4B	
				Packaging 3 - 28 - B4B	
				Packaging 3 - 29 - B4B	
				Packaging 3 - 30 - B4B	
				Packaging 3 - 31 - B4B	
				Packaging 3 - 32 - B4B	
				Packaging 3 - 33 - B4B	
				Packaging 3 - 34 - B4B	
				Packaging 3 - 35 - B4B	
				Packaging 3 - 36 - B4B	
180 QC 21 - SA	1 pcs	4/18/19	0.00 0.00	QC 21 - SA - 21	
				QC 21 - SA - 70	DAS 21 APR 26 2019
				QC 21 - SA - 53	
Part Op 100 - Mori Seiki CNC Lathe Large) 1-Fill tube with sand & install plugs DT8531 on both ends as per Folio FA248 3-Turn Descriptions: first side as per Folio FA248 110 - (QC2- Inspect parts off machine FAI/FAIB) 120 - (Mori Seiki CNC Lathe Large) 1-Turn second side as per Folio FA248 4-Scribe part # and batch # using vibrating stylus as per Dwg D407-667-245 130 - (QC2- Inspect parts off machine FAI/FAIB) 140 - (QC8- Inspect parts - second check) 145 - (Crosstubes) Grind off circumferential machining marks longitudinally. 150 - (Crosstubes) 1- handfinish X-TUBE INSIDE AND OUT 2- ACID ETCH X-TUBE INSIDE AND OUT. USE RED SCOTCH BRITE 160 - (QC7-Inspect Chemical Conversion Coat) 170 - Identify and stock in kanban rack 180 - (QC21- Final Inspection - Work Order Release)					
Job BOM					
Part / Item	Component Name	Quantity	Operation	Container	
D6011-115	Crosstube Material	1 pcs (1 ea)	100-Mori Seiki TL-40 - 1	5006659	
Job Allocations					
Operation	Component Part	Required	Inventory	Allocated	
100-Mori Seiki TL-40 - 1	D6011-115	1	60	0	
Part Specifications					
Specifications could not be found.					



Dart Aerospace Ltd.
1270 Aberdeen Street
Hawkesbury, ON K6A 1K7
CANADA
TEL.: 1 613 632-5200
Email: sales@dartaero.com
www.dartaerospace.com

Plex 4/10/19 12:39 PM dart.leroux.jason

Container No: S174350



Part: D407-667-205TRN

Job No: 193312

Serial No/Batch: S174350

Revision: G

Inspector:

Exp Date:

Instructions:

Date: 04/23/19

①

DART AEROSPACE LTD		Work Order: 193312
Description: Crosstube Assembly		Part Number: D407-667-245
Inspection Dwg: D407-667-245 Rev: G		Page 1 of 2


FIRST ARTICLE INSPECTION CHECKLIST

	Inspection Sheet Drawing Dimension	Tolerance	Actual Dimension	Accept	Reject	Method of Inspection	Comments
SIDE A	2.490	+0.005/-0.000	2.492	✓		CNC-04	
	1.832	+0.005/-0.000	1.837	✓		CNC-08	
	1.838	+0.005/-0.000	1.843	✓		↓	
	1.892	+0.005/-0.000	1.897	✓			
	2.052	+0.005/-0.000	2.057	✓		CNC-04	
	2.206	+0.005/-0.000	2.210	✓		↓	
	2.521	+0.005/-0.000	2.526	✓		↓	
	2.633	+0.005/-0.000	2.638	✓			
	4.10	+/-0.030	4.10	✓		CNC-08	
	4.978	+/-0.030	4.986	✓		↓	
	2.040	+0.000/-0.010	2.035	✓		↓	
	0.125	+/-0.010	.125	✓		↓	
	R0.063	+/-0.010	.063	✓		RG	
	R0.500	+/-0.010	.500	✓		"	
SIDE B	2.490	+0.005/-0.000	2.492	✓		CNC-04	
	1.832	+0.005/-0.000	1.837	✓		CNC-08	
	1.838	+0.005/-0.000	1.842	✓		↓	
	1.892	+0.005/-0.000	1.897	✓			
	2.052	+0.005/-0.000	2.056	✓		CNC-04	
	2.206	+0.005/-0.000	2.211	✓		↓	
	2.521	+0.005/-0.000	2.526	✓		↓	
	2.633	+0.005/-0.000	2.638	✓		↓	
	4.10	+/-0.030	4.10	✓		CNC-08	
	4.978	+/-0.030	4.993	✓		↓	
	2.040	+0.000/-0.010	2.036	✓		↓	
	0.125	+/-0.010	.119	✓		↓	
	R0.063	+/-0.010	.063	✓		RG	
	R0.500	+/-0.010	.500	✓		"	
	112.91	+/-0.020	112.91	✓		Tape	

①

DART AEROSPACE LTD		Work Order: 193312
Description: Crosstube Assembly		Part Number: D407-667-245
Inspection Dwg: D407-667-245 Rev: G		Page 2 of 2

WALL THICKNESS MEASUREMENT



Location	WALL THICKNESS MEASUREMENT (IN)				Deviation Δw (max-min)	TOLERANCE
	w1	w2	w3	w4		
READING 1 L= 0"	.225	.226	.226	.222	.004	0.075"
READING 2 L= 18.82	.227	.267	.248	.209	.058	
READING 3 L= 37.64	.400	.433	.413	.384	.049	
READING 4 L= 56.46	.643	.658	.663	.649	.020	
READING 5 L= 75.27	.390	.406	.421	.406	.031	
READING 6 L= 94.09	.217	.246	.258	.233	.041	
READING 7 L= 112.91	.221	.225	.226	.223	.005	

Calibration Result

Actual Block Thickness: 100-750

Sitescan 250 Measured Thickness: 100-750

Measured by: DAS 66	Audited by: DAS 67	Preliminary Approval:
Date: 2019-04-24	Date: 19-04-25	Date:

Rev	Date	Change	Revised by	Approved
A	04.04.21	New Issue (P/O D407-667-205)	KJ/RF	
B	06.03.09	Dwg Rev updated	KJ/JLM	
C	06.03.30	Tolerance revised for 4.978 dimension	KJ/JLM	
D	07.02.19	Dwg Rev updated	KJ/JLM	
E	09.05.20	Dwg Rev updated	KJ	
F	12.06.04	Wall thickness form added	KJ	
G	15.05.14	Dwg Rev updated	KJ	

Item	QTY	PART NUMBER	DESCRIPTION
	-245		
	X	D407-667-245	CROSSTUBE ASSEMBLY (407 HIGH AFT)
1	1	D6011-115	CROSSTUBE
2	2	D2873-043	NUT PLATE
3	2	D2873-045	NUT PLATE
4	1	D2894-1	SUPPORT
5	2	D3190-1	CHAFING SHIELD
6	2	D3595-063-430	RUBBER CUSHION
7	14	MS20601AD4W8	RIVET (OR NAS9302B-4-8)
8	4	MS21920-22	CLAMP
9	2	MS21920-25	CLAMP (OR MS21920-24)
10	AR	SCOTCH-WELD DP460	EPOXY ADHESIVE, 3M SCOTCH-WELD
11	AR	PROSEAL 890	SEALANT

GENERAL NOTES:

- 1) MATERIAL: MANUFACTURED FROM D6011-115
FINISHED LENGTH = 112.91±0.020
- 2) FINISH: CHEMICAL CONVERSION COAT PER DART QSI 005 4.1
PRIME INSIDE AND OUTSIDE PER DART QSI 005 4.2
PAINT CROSSTUBE PER DART QSI 005 4.2
FOR HATCHED AREAS (ZN A5-2), MASK AS REQUIRED
TO APPLY PRIME AND APPLY CLEAR COAT ONLY
- 3) TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED.
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED.
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX.
- 6) IDENTIFICATION: SCRIBE DART PART NUMBER "D407-667-245" AND BATCH NUMBER ON INSIDE OF CLIFF USING VIBRATING STYLUS.
- 7) WEIGHT: 27.7 lbs
- 8) PART IS SYMMETRIC ABOUT CENTERLINE.
- 9) RUN-OFF PART. BLEND OUT EDGE LONGITUDINALLY. TRANSITION SHOULD BE SMOOTH.
- 10) BEND PROGRESSIVELY WITH A MINIMUM OF 6 PASSES. MAXIMUM TUBE FLATTENING DUE TO BENDING IS 8% BASED ON O.D.
- 11) LIQUID PENETRANT INSPECT OUTSIDE SURFACE OF CROSSTUBE PER QSI 038.
- 12) INSTALL D2894-1 CENTER SUPPORT USING A 0.04" TO 0.07" THICK LAYER OF SCOTCH-WELD DP460 PER QSI 015. LET CURE FOR 24 HOURS AFTER INSTALLATION AND PRIOR TO PACKAGING.
- 13) INSTALL MS21920-25 CLAMPS WITH D3595-063-430 RUBBER CUSHIONS TO SECURE D2894-1 SUPPORT ON TOP SIDE OF THE CROSSTUBE. ENSURE CLAMPS ARE OPPOSITE CROSSTUBE SUPPORT.
NOTE: MS21920-24 CLAMPS CAN BE USED TO ACCOMMODATE VARYING DIAMETERS. ENSURE THERE IS A MINIMUM OF 1.5 THREADS IN SAFETY ON THE NUTS.
- 14) EXTREME CARE MUST BE TAKEN TO PROTECT THE OUTSIDE SURFACE OF THE TUBE. THE OUTSIDE SURFACE MUST BE SMOOTH AND FREE FROM SURFACE DEFECTS SUCH AS SCRATCHES, NICKS, OR DENTS. DEFECTS UP TO 0.005" MAY BE BLENDED OUT LONGITUDINALLY. CIRCUMFERENTIAL GRIND MARKS ARE UNACCEPTABLE.
- 15) APPLY A THIN COAT OF PROSEAL 890 ON INSIDE CONCAVE SURFACE OF D3190-1 CHAFING SHIELDS AND LET CURE PER MANUFACTURER'S INSTRUCTIONS. INSTALL PROSEAL D3190-1 CHAFING SHIELDS ONTO CROSSTUBE BY APPLYING A THIN COAT OF PROSEAL 890 ONTO CROSSTUBE. BE SURE TO ELIMINATE ANY AIR GAPS.
- 16) INSTALL D3190-1 CHAFING SHIELDS SO THAT OVERLAP IS 50 TO 70 DEGREES FROM BOTTOM OF CROSSTUBE OPPOSITE D2894-1 SUPPORT.
- 17) TORQUE CLAMPS 80 TO 100 IN-LB. TORQUE CLAMPS ON D3190-1 CHAFING SHIELD 40 TO 50 IN-LB. ENSURE AT LEAST 1.5 THREADS ARE SHOWING IN SAFETY AND THAT NUT HAS NOT BOTTOMED-OUT AFTER TORQUING. PRIOR TO PACKAGING, RE-CHECK TORQUE ON CLAMPS AFTER ADHESIVE HAS CURED FOR 24 HOURS.

RELEASED

2015 APR 09

4P ECU 15-517

G	INCORP. DEO'S D407-667-245-F1/F2 (ZN D6-1, A8-1, D5-2, B6-2, C6-2); 8.90 WAS 8.53 (ZN D5-2); TORQUE REDUCED FOR CHAFING SHIELD (ZN A8-1); FINISH REVISED TO ALLOW MANUFAC. FLEXIBILITY (ZN C8-1)	RF	15.03.20
F	REFORMAT NOTES TO NEW STANDARDS (ZN B9-1); RELOCATED FLAG # 6 (ZN A8-3) PER NCR 210; REMOVED REF. & ADD TOLERANCES (ZN C6-3, C4-3 & D2-3)	RF	08.11.06
E	8.02 AND 8.53 WERE 8.40 AND 8.90 (ZN D5-2); REORGANIZED VIEWS AND REFORMAT DRAWING TO CURRENT STANDARDS. REASONS: CLAMPS MOVED 0.375 TOWARD CL TO ELIMINATE INTERFERENCE WITH AIRCRAFT MOUNTS. REFERENCE: PAR#08-21 AND ECU#1225	MB	08.07.24
D	ADD VIEW FOR OEM SKID HOLES, ROTATE ORIENTATION OF CLAMPS SECTION F-F. REMOVE -851 ABRASION STRIP, ADD MAGNOBOND 6398, ADD CUSHION	PH	07.02.07
C	ADD HOLES AND NUT PLATES FOR COMPATIBILITY WITH BHTAA SKIDTUBES	PH	05.07.26
B	ADD CHAFING SHIELD	CP	03.05.21
A	NEW ISSUE	CP	02.05.13
REV.	DESCRIPTION	BY	DATE
DESIGN	4P		
DRAWN	RF		
CHECKED	4P		
MFG. APPR.	4P		
APPROVED	4P		
DE APPR.	4P		
DATE	15.03.20		
DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA DRAWING NO. D407-667-245 TITLE CROSSTUBE ASSY (407 HIGH AFT) REV. G SHEET 1 OF 4 SCALE NTS COPYRIGHT © 2002 BY DART AEROSPACE LTD THIS DOCUMENT IS UNCLASSIFIED AND IS RELEASED ON THE EXPIRATION DATE THAT IT IS NOT TO BE USED FOR ANY PURPOSES OF COPIED OR TRANSMITTED TO ANY OTHER PERSON WITHOUT THE WRITTEN PERMISSION OF DART AEROSPACE LTD.			

